

PIG Well Pad Liner — 65 mil

Product Information:

Use this versatile liner for secondary containment needs during drilling, fracturing and refracturing operations.

- Polypropylene composite consists of three barrier films sandwiched by double layers of needle-punched with heat-fused surfaces
- Offers 1.5X more tear resistance and 4X more puncture resistance than standard 30-mil HDPE liners
- High-traction surface minimizes slip-and-fall injuries in wet or dry conditions
- Versatile liner can be used to create secondary containment structures on-site for frac tanks, cylindrical tanks and drill cuttings
- Welds easily for liquidtight installation
- Won't stretch or crack like HDPE
- Patent No. 9,517,596



PIG® Well Pad Liner – 65 mil			
Item #	Master Roll Approx. Dimensions	Approx. Weight	Color
MAT4500	18'W x 465'L	873 lbs.	Dark Gray

Always in stock. 24/7 customer service. Contact your New Pig Energy sales representative for pricing details.

**Need a custom solution for your drilling operation?
Call the New Pig Energy secondary containment
experts at 1-855-PIG-LINER (744-5463).**

See back for additional product specifications.



Phone: 1-855-PIG-LINER
Email: pigliner@newpigenergy.com
Online: newpigenergy.com

PIG, PIG logo are registered trademarks in USA and other countries. See tm.newpig.com

PIG Well Pad Liner — 65 mil

Product Specifications:

MAT4500

Composition:	Polypropylene
Color:	Dark Gray
UV Resistant:	Yes
Master Roll Width:	18' (5.5 m)
Thickness:	65 mil
Approximate Roll Length:	465' (141.73 m)
Approximate Roll Weight:	873 lbs. (395.99 kg)
Core Dia.:	4" (10.2 cm)
Recyclable:	Yes

Testing Information:

MATERIAL	THICKNESS	TENSILE PROPERTIES (MAX STRENGTH)		PUNCTURE RESISTANCE	TEAR RESISTANCE	
PIG Well Pad Liner – 65 mil	ASTM D 5994	ASTM D 6693/GRI, 2 ipm rate		ASTM D 4833	ASTM D 1004 (lbs.)	
	Mils	A-Break lb/in-width	B-Break lb/in-width	(lbs.)	A	B
	67	84	65	214	47	38

Top Side Absorbency: Water = 1.09 gal/100 sq ft; Oil = 1.19 gal/100 sq ft

Permittivity (ASTM D 4491) = 0

Calculated Darcy Coefficient of Permeability = 0



New Pig Energy

*Secondary Containment
from the Leak & Spill Experts.®*

Phone: 1-855-PIG-LINER

Email: pigliner@newpigenergy.com

Online: newpigenergy.com